

AUSTRALIA'S MARKET LEADER

GLOBE POWER



DIESEL LIGHTING TOWER



GP6UrbanD

HYDRAULIC LEGS

GENERAL

Light Power 6 x 350W 48V DC
 Lights LED
 Lumen Output 315,000

GENSET

Generator Kubota 1105
 Fuel Type Diesel
 Fuel Consumption 1.1L/hr
 Running Time 145 hours
 Alternator Sincro FB4-48/100, 48V DC
 Noise Level 68dBA at 7m
 Control System Electronic genset control module with auto stop/start

MAST

Mast Height (Max) 8.10m
 Mast Type Hydraulic
 Mast Rotation 350° non-continuous
 Mast Max Horizontal Outreach 3m
 Mast Lift Time 110 seconds
 Mast Lower Time 90 seconds
 Telescope, Tilt Hydraulic
 Hydraulic System Pump 12V DC
 Function Control Electric over hydraulic

Dimensions (Stowed) 3500 x 2700 x 1785 mm
 Dimensions (Deployed) 8100 x 3500 x 1800 mm
 Weight 1706 kg

TRAILER

Wheels 16" x 6 Trac 2 rims
 Tyres 235/R16 x 16"
 Towing Speed (Max) 80km/hr
 Fuel Tank Capacity 140L
 Bunded 110%
 Wind Speed Rating (Max) 100km/hr

