



## Genie Self-Propelled Scissor Lifts GS<sup>™</sup>-1330m

### **Specifications**

Model	GS™-1330m	
Measurements	Metric	US
Working height maximum*	5.81 m	18 ft 6 in
A Platform height maximum	3.81 m	12 ft 6 in
A Platform height - stowed	0.90 m	2 ft 11 in
Platform length - outside	1.26 m	4 ft 2 in
extended	1.72 m	5 ft 8 in
Slide-out platform extension deck	0.46 m	1.5 ft
A Platform width - outside	0.67 m	26.5 in
Guardrail height	1.10 m	3 ft 7 in
Toeboard height	0.15 m	6 in
A Height - stowed, fixed rails	2.02 m	6 ft 7.5 in
Length - stowed	1.41 m	4 ft 8 in
- stowed extended	1.87 m	6 ft 2 in
🛕 Width	0.78 m	30.5 in
Wheelbase	0.98 m	3 ft 3 in
🛕 Ground clearance - centre	6 cm	2.4 in
🛕 - with pothole guards deployed	2 cm	0.83 in
Productivity		
Max platform occupancy (indoor/outdoor)**	2/-	2/-
Lift capacity	227 kg	500 lb
Lift capacity - extension deck	91 kg	200 lb
Drive height	Full height	
Drive speed - stowed	4.0 km/h	2.5 mph
Drive speed - raised	0.8 km/h	0.5 mph
Gradeability - stowed***	25%/14°	25%/14°
Turning radius - inside	40 cm	15.7 in
Turning radius - outside	1.55 m	5 ft 1 in
Raise/lower speed	20 / 22 sec	
Controls	Proportional	
Drive	dual rear wheel, electric	
Brakes	dual rear wheel, electric	
Tyres solid non-marking	25.4 x 7.6 cm	10 x 3 in
Power		
Power source	24 V DC (two 12 V 85 Ah batteries)	
Hydraulic system capacity	1.5 gal	5.6 L



Standards Compliance

AS 1418.10


1,953 lb


887 kg

\* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height. \*\* Indoor use only for the GS-1330m \*\*\* Gradeability applies to driving on slopes, see Operator's Manual for details regarding slope ratings. \*\*\*\* Weight will vary depending on options and/or country standards.

A Λ

Δ





www.genielift.com.au

# **\** 13 40 00

# www.accesshire.net





### Genie Self-Propelled Scissor Lifts GS<sup>™</sup>-1330m

### Features

### Standard Features

#### **Measurements**

#### GS-1330m

- 5.81 m (18 ft 6 in) working height
- Up to 227 kg (500 lb) lift capacity

#### Productivity

- Folding rails with half-height swing gate
- Dual rear wheel DC electric drive
- Smart Link<sup>™</sup> control system (joystick, 2) lift speeds & 2 selectable proportional drive speeds, user-friendly diagnostics)
- Rear charger receptacle
- Platform control with battery charge indicator
- On-board diagnostic system
- AC power to platform
- Lanyard attachment points
- Manual platform lowering valve
- Emergency stop at both platform and ground controls
- Dual rear wheel electric brakes
- Electric brake release
- Swing-out component trays
- Pothole guards
- Tilt level sensor with audible alarm
- Descent alarm
- Motion alarm
- Dual flashing LED beacons
- Automotive horn
- Hour meter

#### Power

- 24 V DC battery pack
- Universal 20 amp smart charger

### Platform

- 1.26 m x 0.67 m (50 x 26.5 in) steel platform
- 0.46 m (1.5 ft) extension deck

#### Power

24 V DC (two 12V 85 Ah batteries)

Solid non-marking

### **Options & Accessories**

#### **Productivity Options**

• Power to platform: plug, socket, with optional Residual-current Circuit Breaker with Overcurrent protection

#### **Power Options**

• AGM maintenance-free batteries



#### Genie - Toll free number 1800 788 633 Genie USA Distributed By: 18340 NE 76th Street Sydney Brisbane Melbourne Adelaide Perth Darwin P.O. Box 97030 HEAD OFFICE 33 Kimberley Street 16-18 Nixon Road 126 Sheffield Road Redmond, Washington 74 Glendenning Road 133 Logis Boulevard 33 McCourt Road Darra QLD 4076 Glendenning NSW 2761 Dandenong Sth VIC 3175 Wingfield SA 5013 Welshpool WA 6106 Yarrawonga NT 0830 98073-9730

Effective Date: May, 2018. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Genie is a registered trademark of Terex South Dakota, Inc. @ 2018 Terex Corporation.

GS-1330m 190518

www.genielift.com.au

# **13 40 00**

## www.accesshire.net

- **Tyres**