

10MSP

MOBILE STOCK PICKER



Performance

Platform Height	3.05 m
Working Height	5.05 m
Stowed Height	1.42 m
Drive Height	Max. Platform Height
Platform Entry Height	0.33 m
Platform Size (W x L)	0.69 x 0.51 m
Parcel Tray Size (W x L)	0.71 x 0.65 m
Overall Vehicle Chassis Length	1.52 m
Overall Vehicle Chassis Width	0.84 m
Chassis Width w/o bumper	0.75 m
Weight	500 kg
Platform Capacity	
Stock Picking Platform	160 kg
Carry Deck	115 kg
Material Tray	115 kg
Drive Maximum Speed	
Platform Lowered	5.5 km/h
Platform Elevated	1.0 km/h
Inside Turning Radius	Zero
Gradeability	15%

Standard Specifications

Power

Batteries	4 x 6V 210AH AGM
Battery Charger	25 Amp Automatic
Drive System	4 Brush Direct Electric (planetary gear)

Tyres

Tyre Material	Non marking
Rear Drive & Steer Wheels	0.32 x 0.10 m
Front Caster Wheels	0.20 x 0.06 m

Standard Features

- Heavy Duty Planetary Gear Drive Motors with 5 Times the Life of Previous Models
- Single Heavy Duty Pistol-Grip Joystick
- 4 Brush Direct Electric Drive
- Point & Go® One-Hand Drive and Steer System
- Proportional Drive and Elevate Controls
- Four Sealed 210 amp-hr Maintenance-Free Glass Mat (AGM) Batteries
- Automatic Five-Hour Battery Charger
- Battery Discharge Indicators — Platform and Base
- Heavy-Duty Anodized Aluminum Mast Sections
- Maintenance-Free Mast Guide System
- Strobe Lights Front and Rear
- Motion Alarm
- Slope Cut-Out Control Interlock
- Stand-On Foot Switch Operation Enable Control



- Platform Gate Operation Interlock
- Adjustable Height Material Tray
- Built-in Fork Truck Pockets
- Hourmeter
- Horn
- Transportation Tie Downs
- Side and Front Bumper
- Guide Roller System
- AS / NZS 1418.10 Compliant

Accessories & Options

- Programmable 4-Digit Security Lock
- Fluorescent Light Tube Caddy

Increased Productivity

- Lift and carry up to 275 kg (people and materials), at working heights up to 5.05 m
- Extra-large material tray handles more boxes, supplies and tools
- Preventive maintenance programs keep machines in top working condition and lower your cost of ownership

More Versatility

- Clean design and non-marking tyres
- Advanced joystick controller provides one-handed control
- Zero turning radius; MSP Series turns on its own axis
- Compact design ideal for working in confined areas — warehouses, stores, office areas, schools, and other indoor environments

The JLG "1 & 5" Warranty

JLG Industries, Inc. backs its products with its exclusive "1 & 5" Warranty. We provide coverage on all products for one (1) full year and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds AS/NZS 1418.10 2011 as originally manufactured for intended applications.



JLG Industries (Australia)

358 Park Road
Regents Park, NSW 2143
Telephone 02 8718 6300
Fax 02 8718 6377
www.jlg.com.au

An Oshkosh Corporation Company