

20MVL

MOBILE VERTICAL LIFT



Performance

| | |
|------------------------------|----------------------|
| Platform Height | 5.94 m |
| Working Height | 7.94 m |
| Drive Height | Max. Platform Height |
| Stowed Height | 198 cm |
| Platform Entry Height | 46 cm |
| Platform Size (W x L) | |
| Extension Platform | 120 x 66 cm |
| Parcel Tray Platform | 66 x 66 cm |
| Stock Picking Tray Size | 71 x 64 cm |
| Overall Vehicle Length | |
| Extension Platform Retracted | 150 cm |
| Parcel Tray Platform | 165 cm |
| Overall Vehicle Width | |
| Extension Platform | 82 cm |
| Parcel Tray Platform | 82 cm |
| Gross Vehicle Weight | |
| Extension Platform | 1,055 kg |
| Parcel Tray Platform | 1,055 kg |
| Platform Capacity | |
| Extension Platform | 160 kg |
| Parcel Tray Platform | 115 kg |
| Stock Picking Tray | 45 kg |
| Drive Maximum Speed | |
| Platform Lowered | 5.6 km/h |
| Platform Elevated | 1 km/h |
| Turning Radius | Zero |
| Gradeability | 20% |
| Underclearance | 5 cm |

Standard Specifications

Power Source

| | |
|-----------------|--|
| Batteries | 4 x 6V Deep Cycle AGM |
| Battery Charger | 25 Amp; 5-Hour Charge |
| Drive System | 4 Brush Direct Electric (planetary gear) |

Tyres

| | |
|---------------------------|-------------|
| Rear Drive & Steer Wheels | 32 x 10 cm |
| Front Caster Wheels | 20 x 6 cm |
| Tyre Material | Non-Marking |



Standard Features

- Heavy Duty Planetary Gear Drive Motors
- Low Maintenance Anodized Aluminum Mast
- Safety Interlocked Controls
- Pistol-Grip Platform Control
- Single Joystick Drive and Steer Control—Solid State, Microprocessor Controlled
- Variable Speed Elevation Controls
- Automatic Pothole Protection System
- 1-1/2 Degree Tilt Alarm and Control
- Key Lock Main Power Switch
- Automatic Power-Off Battery Saver Control
- Battery Discharge Indicators—Platform and Base
- Transportation Tie Downs
- Built-In Fork Truck Pockets
- Hourmeter
- All Motion Alarm
- Flashing Amber Beacon
- Lifting Eye for a Crane Hook
- Horn
- AS/ NZS 1418.10 Compliant

Accessories & Options

- Programmable 4-Digit Security Lock
- Fluorescent Light Tube Caddy
- Tool Tray (20 x 45 x 12.5 cm)
- AC Outlet to Platform

The JLG "1 & 5" Warranty

JLG Industries, Inc. backs its products with its exclusive "1 & 5" Warranty. We provide coverage on all products for one (1) full year and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/ or equipment changes without prior notification. This machine meets or exceeds AS/NZS 1418.10 2011 as originally manufactured for intended applications.



JLG Industries (Australia)

358 Park Road
Regents Park, NSW 2143
Telephone 02 8718 6300
Fax 02 8718 6377
www.jlg.com.au

An Oshkosh Corporation Company