

Aerial Work Platforms Genie[®] Runabout[™]

Specifications

Genîe

MODEL	GR-15		GR-20		
Measurements	Metric	US	Metric	US	
Working height*	6.47 m	20 ft 8 in	8.02 m	25 ft 9 in	
Platform height	4.47 m	14 ft 8 in	6.02 m	19 ft 9 in	
A A Platform dimensions (length x width)					
Standard with extension	1.40 m x 75 cm	55 x 29.5 in	1.40 m x 75 cm	55 x 29.5 in	
A Height - stowed	1.57 m	5 ft 2 in	1.98 m	6 ft 6 in	
- stowed with chain guard	-	-	2.05 m	6 ft 9 in	
🛕 Length - stowed	1.35 m	4 ft 5 in	1.35 m	4 ft 5 in	
A Width	75 cm	2 ft 5.5 in	80 cm	2 ft 7.5 in	
🛕 Ground clearance - center	6.4 cm	2.5 in	6.4 cm	2.5 in	

227 kg

4.0 km/h


0.8 km/h

1.32 m

21 / 19 sec

25 x 8 x 20 cm





Power

Controls

Productivity

Drive speed - stowed

Drive speed - raised

Turning radius - inside

Turning radius - outside

Tyres - solid non-marking

Raise / lower speed

Lift capacity

Gradeability**

Max platform occupancy (indoor/outdoor)1

Power source	24V (four 6V 225 Ah batteries)			
Hydraulic system capacity	8.33 L	2.2 gal	8.33 L	2.2 gal

Sound & Vibration Levels

Sound pressure level (ground workstation)		<70 dB	A	
Sound pressure level (platform workstation)		<70 dB	A	
Vibration	<2.5 m/s ²	<98.4 in/s ²	<2.5 m/s ²	<98.4 in/s ²
Weight***				
	1026 kg	2,261 lbs	1,148 kg	2,529 lbs

Standards Compliance

ANSI A92.6, CSA B354.2, CE Compliance, AS 1418.10

1/-

30%

zero

24V DC proportional

159 kg

4.0 km/h

0.8 km/h

1.35 m

24 / 21 sec

25 x 8 x 20 cm

350 lbs

2.5 mph

0.5 mph

4 ft 5 in

24 / 21 sec

10 x 3 x 8 in

www.accesshire.net

500 lbs

2.5 mph

0.5 mph

4 ft 4 in

21 / 19 sec

10 x 3 x 8 in

¹ Indoor use only. * The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height. ** Gradeability applies to driving on slopes, See operator's manual for details regarding slope rating. *** Weight will vary depending on options and/or country standards.

<u>****</u> 13 40 00

www.genielift.com.au





Genie Aerial Work Platforms Genie[®] Runabout[™]

Features

Standard Feature

Measurements

GR-15

- 6.47 m (20 ft 8 in) working height
- 4.47 m (14 ft 8 in) platform height
- Up to 227 kg (500 lbs) lift capacity

GR-20

- 8.02 m (25 ft 9 in) working height
- 6.02 m (19 ft 9 in) platform height
- Up to 159 kg (350 lbs) lift capacity

Productivity

- Smart Link™ control system (joystick, proportional lift & 2 selectable proportional drive speeds, user-friendly diagnostics)
- Auxiliary platform lowering
- Low 39 cm (15.5 in) platform entry height
- Work station tray (GR-15 only)
- Patented rigid mast system
- Compact base 75 cm x 1.35 m (29.5 x 53 in) (GR-15 only)
- Ground clearance 6.4 cm (2.5 inches) (stowed)
- Battery charge indicator
- On-board diagnostic system
- Descent and tilt alarm
- · Zero inside turning radius
- · Dual wheel brakes
- Hydraulic brake release
- Pothole protection
- · Hinged rear ABS covers for easy access to all major electrical and hydraulic components
- Tie down attachment points
- Overhead crane attachment point
- Large forklift pockets access
- Certified load sensor
- Dual flashing beacons
- Motion alarm
- Automotive-style horn
- Drive cutout while charging

Standard Features

Platform

• 1.40 m x 75 cm (55 x 29.5 in) platform with 51 cm (20 in) extension and sliding midrail

Power

• 24V (four 6V 225 Ah batteries) with automatic 25 amp battery charger

Tyres

• Non-marking solid

Options & Accessories

Productivity Options

- 240 V power to platform
- Biodegradable hydraulic oil

Power Options

· AGM maintenance-free batteries



Genie - Toll free number 1800 788 633

Brisbane HEAD OFFICE	Sydney	Melbourne	Adelaide	Perth	Darwin	18340 NE 76th Street P.O. Box 97030
33 Kimberley Street	74 Glendenning Road	133 Logis Boulevard	16-18 Nixon Road	126 Sheffield Road	33 McCourt Road	Redmond, Washington
Darra QLD 4076	Glendenning NSW 2761	Dandenong Sth VIC 3175	Wingfield SA 5013	Welshpool WA 6106	Yarrawonga NT 0830	98073-9730

Effective Date: July, 2015. Product specifications and prices are subject to change without notice or obligation. The photographs and/or drawings in this document are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. The only warranty applicable to to our equipment is the standard written warranty applicable to the particular product and sale and we make no other warranty, express or implied. Products and services listed may be trademarks, service marks or trade names of Terex Corporation and/or their subsidiaries in the USA and many other countries. Genie is a registered trademark of Terex South Dakota, Inc. © 2015 Terex Corporation.

GS15-20 171126

www.genielift.com.au

13 40 00

www.accesshire.net

- Genie USA Distributed By: