



DIESEL GENERATOR

Powered By:



GP412DZ

GENERAL

Model	GP412DZ
Power Type	Diesel
Prime Power (kW/kVA)	300/376
Standby Power (kW/kVA)	330/413
Rated Current	521AMPS
Operating Ambient Temp.	50°C

ENGINE

Engine Model	Deutz BF6M1015CP-LAG
Aspiration	Turbo-charged charge air cooled
No. of Cylinders	6
Governor Type	Electronic Governor
Lubricating Oil Capacity	38L

ALTERNATOR

Model	GP314F1
Frequency	50/60
Rate Power (kW/kVA)	304/380
Power Factor	0.8
Exciter Type	Self-excited
Voltage Regulator	AS440
Voltage Regulation	±1.0%
No. of Phases	3
Insulation	Class H
Protection	IP21
Altitude	1000m

NOISE LEVEL

Sound Pressure at 7m/dB 74

UNIT

Dimensions (LxWxH)	4201 x 1500 x 2300
Dry Weight	4800kg

FUEL CONSUMPTION

Fuel Consumption*	61.6(L/h)
Fuel Tank Capacity	1660L

SAFETY FEATURES

ISO Compliant
Outlet package with AS3000 compliant RCD protection
Emergency E Stop

CONTROL SYSTEM

Operator friendly DSE control system

ENCLOSURE FEATURES

Sound attenuated canopies
Powder coated finish
IP65 rating
Fully bunded extended run fuel tanks

WARRANTY

12 months warranty, further options available

STANDARD OPTIONS INCLUDED

Remote Monitoring

*Fuel consumption based on 75% load