## **AUSTRALIA'S MARKET LEADER**



**DIESEL GENERATOR** 

Powered By:













## GP550V

## **GENERAL**

Model Power Type Prime Power (kW/kVA) Standby Power (kW/kVA)

Rated Current Operating Ambient Temp.

ENGINE

**Engine Model** Aspiration

No. of Cylinders Governor Type Lubricating Oil Capacity

Model Frequency Rate Power (kW/kVA) Power Factor **Exciter Type** Voltage Regulator Voltage Regulation No. of Phases Insulation Protection

**NOISE LEVEL** 

Altitude

Sound Pressure at 7m/dB 76

**GP550V** Diesel 400/500 440/550 695AMPS 50°C

**VOLVO TAD1641GE** 

aftercooled

EMS2 48L

Turbocharged & low temp

**ALTERNATOR** 

GP354D1 50/60 400/500 0.8 **PMG** MX341

±1.0%

Class H IP21 1000m

Remote Monitoring

UNIT

Dimensions (LxWxH) Dry Weight

**FUEL CONSUMPTION** 

Fuel Consumption\* **Fuel Tank Capacity**  77.2(L/h) 2400L

6930kg

5100 x 1900 x 2430

**SAFETY FEATURES** 

ISO Compliant

Outlet package with AS3000 compliant RCD protection Emergency E Stop

**CONTROL SYSTEM** 

Operator friendly DSE control system

**ENCLOSURE FEATURES** 

Sound attenuated canopies Powder coated finish

IP65 rating

Fully bunded extended run fuel tanks

**WARRANTY** 

12 months warranty

STANDARD OPTIONS INCLUDED

\*Fuel consumption based on 75% load