



Self-propelled Vertical Lifts

PARAMETER

Model	AMWP8-1200	AMWP9.5-1200
S.W.L	159kg	136kg
Max. Occupants	1	1
Max. Working Height A	8.00m	9.50m
Max. Platform Height B	6.00m	7.50m
Overall Length C	1.39m	1.44m
Overall Width D	0.80m	0.80m
Overall Height E	1.99m	1.99m
Platform Size(Length F /Width G)	0.71m×0.75m	0.71m×0.75m
Platform Extension Size H	0.53m	0.53m
Ground Clearance(Stowed)	0.06m	0.06m
Ground Clearance(Raised)	0.019m	0.019m
Wheelbase	1.07m	1.12m
Turning Radius(Inside/Outside)	0/1.55m	0/1.60m
Drive Motor	2×24VDC/1kW	2×24VDC/1kW
Lifting Motor	24VDC/2kW	24VDC/2kW
Travel Speed(Stowed)	4km/h	4km/h
Travel Speed(Raised)	1.1km/h	1.1km/h
UP/Down Speed	23/25sec	29/32sec
Batteries	2×12V/100Ah	2×12V/100Ah
Integrated Charger	24V/15A	24V/15A
Gradeability	25%	25%
Max. Working Slope	X-1.5°/Y-3°	X-1.5°/Y-3°
Tyres	Φ323×100mm	Φ323×100mm
Weight	1120kg	1480kg

Standard Equipment

Cylinder Holding Valve
 Emergency Stop Button
 Two Controllers Operation
 Emergency Lowering System
 Leveling Sensor
 Forklift Pockets
 All Motion Alarm
 Transport Tie Hole
 Battery Charge Indicator
 Electric Limit Switch
 Automatic Pothole Protection
 Drivable At Full Height
 Overload Sensor With Alarm
 Onboard Diagnostic System
 Flashing Beacon

Options

AC Power to Platform

