



(Only For GTWY12.5/14-1300)

Mobile Vertical Lifts

PARAMETER

Model	GTWY9.5-1300	GTWY11-1300	GTWY12.5-1300	GTWY14-1300
S.W.L	150kg	150kg	150kg	136kg
Max. Occupants	1	1	1	1
Max. Working Height A	9.50m	11.00m	12.50m	14.00m
Max. Platform Height B	7.50m	9.00m	10.50m	12.00m
Overall Length(Stowed) C	1.30m	1.34m	1.53m	1.53m
Overall Length(Tilted Back) D	/	/	2.63m	3.04m
Overall Width E	0.75m	0.75m	0.75m	0.75m
Overall Height(Stowed) F	1.99m	1.99m	2.35m	2.77m
Overall Height(Tilted Back) G	/	/	1.70m	1.95m
Outrigger Footprint H / I	1.70/1.86m	1.70/1.86m	2.08/2.15m	2.08/2.15m
Platform Size(Length/Width)	0.70×0.60m	0.70×0.60m	0.70×0.60m	0.70×0.60m
Ground Clearance	0.055m	0.055m	0.055m	0.055m
Lifting Motor - AC	220VAC/1.5kW	220VAC/1.5kW	220VAC/1.5kW	220VAC/1.5kW
Lifting Motor - DC	12VDC/1.5kW	12VDC/1.5kW	12VDC/1.5kW	12VDC/1.5kW
Up/Down Speed	28/18sec	34/22sec	40/26sec	45/29sec
Batteries	12V/85Ah	12V/85Ah	12V/85Ah	12V/85Ah
Integrated Charger	12V/15A	12V/15A	12V/15A	12V/15A
Tyres(Front Wheels)	8in	8in	8in	8in
Tyres(Back Wheels)	5in	5in	5in	5in
Weight - AC	430kg	450kg	530kg	559kg
Weight - DC	453kg	472kg	553kg	588kg

Standard Equipment

Tilt Back Frame(Only For GTWY12.5/14-1300)

Swing Outriggers With Interlock

Emergency Stop Button

Emergency Lowering System

Easy Loading In Pickup Trucks

Two Controllers Operation

Leveling Sensor

Forklift Pockets

Transport Tie Hole

Deadman Switch

All Motion Alarm

Cylinder Holding Valve

Flashing Beacon

Onboard Diagnostic System

Options

AC Power to Platform

Overload Sensor With Alarm

