



Self-propelled Scissor Lifts(Electric Pint-sized Type)

Model: JCPT1614HD/DC - JCPT1612HDB/DCB - JCPT1612HDS/DCS - JCPT1412HD/DC - JCPT1212HD/DC
JCPT1012HD/DC - JCPT1008HD/DC - JCPT0808HD/DC - JCPT0807HDS/DCS

Electric Pint-sized scissor lifts series uses the battery as the power source, and has two types of DC motor drive and hydraulic motor drive. The maximum working height covers 7.8-15.7m and the maximum load is 450kg. This type of scissor lifts has the advantages of energy saving, environmental protection, zero emissions, no noise, which is suitable for indoor flat ground and higher environmental requirements of the working environment.



Easy Maintenance



Non Marking Tyre



Folding Guardrails



Extended Platform

Model	JCPT1412 HD/DC	JCPT1212 HD/DC	JCPT1012 HD/DC
Size			
Max. Working Height(CE/ANSI)	13.80m	12.00m	10.00m
Max. Platform Height(CE/ANSI)	11.80m	10.00m	8.00m
Overall Length	2.48m	2.48m	2.48m
Overall Width	1.19m	1.15m	1.15m
Overall Height(Rails Up)	2.62m	2.49m	2.36m
Overall Height(Rails Down)	2.09m	1.96m	1.83m
Platform Size(Length×Width)	2.27m×1.12m	2.27m×1.12m	2.27m×1.12m
Platform Extension Size	0.90m	0.90m	0.90m
Ground Clearance(Raised/Stowed)	0.019m/0.10m	0.019m/0.10m	0.019m/0.10m
Wheelbase	1.87m	1.87m	1.87m
Turning Radius(Inside/Outside)	0m/2.20m	0m/2.20m	0m/2.20m
Tyres	φ381×127mm	φ381×127mm	φ381×127mm
Performance			
S.W.L(CE)	320kg	320kg	450kg
S.W.L(ANSI)	250kg	/	/
S.W.L On Extension	113kg	113kg	113kg
Max. Occupants	3	2	2
Gradeability	25%	25%	25%
Travel Speed(Stowed)	HD 3.5km/h , DC 4.0km/h	HD 3.5km/h , DC 4.0km/h	HD 3.5km/h , DC 4.0km/h
Travel Speed(Raised)	0.8km/h	0.8km/h	0.8km/h
Max. Working Slope(CE)	1.5°/3°	1.5°/3°	1.5°/3°
Max. Working Slope(ANSI)	2°/3°	2°/3°	2°/3°
Up/Down Speed	HD 65/38sec , DC 84/38sec	HD 45/36sec , DC 54/42sec	HD 28/38sec , DC 36/33sec
Weight			
Overall Weight(CE)	HD 2840kg , DC 2880kg	HD 2945kg , DC 2965kg	HD 2615kg , DC 2655kg
Overall Weight(ANSI)	HD 3060kg , DC 3100kg	HD 2510kg , DC 2350kg	HD 2215kg , DC 2255kg
Power			
Battery	4×12V/300Ah	4×6V/240Ah	4×6V/225Ah
Charger	24V/30A	24V/30A	24V/30A
Driving Motor	HD / , DC 24V/1.5kW	HD / , DC 24V/1.5kW	HD / , DC 24V/1.5kW
Lifting Motor	24V/4.5kW	24V/4.5kW	24V/3.3kW
Other Configurations			
Drivable At Full Height	4×2 Driving	Forklift Pockets	Automatic Pothole Protection Device