


Sound Proof Diesel Generator

Welders





rail

Railways are the arteries of our society. They move vast numbers of people, livestock, products, and immense quantities of raw materials every day. Damaged or worn rails brings all that to a stop. But, with a Shindaiwa silenced welder on the job, track maintenance or new installation work can be fast, efficient and quiet in sound-sensitive areas. Ensuring precise control over current/voltage delivers optimized puddle performance to the most demanding standards for all root, fill and cap passes.



pipeline

Welding pipe can happen just about anywhere – in the middle of a city, in the middle of a desert, or at the bottom of an ocean. Of course, when big pipes are involved, you'll be ready for our Dual continuous control. It assists you to tune your arc for the pipe, pass, position, conditions and even inside the pipe itself. That's when a powerful, reliable dual operator multi-control Shindaiwa welder really makes sense.



Easy operator interface with 3 way switching in either Welding, Generating or simultaneous modes. Emergency stop and key lockable operation modes.



Preset Current and Voltage Control with easy to read digital output. 14-pin wire feeder, and 9-pin remote control connections.



A fully bunded mine-safe spill containment tank, along with easy access to the spill controls, keeps the worksite clean and safe. Standard on DGW420, and optional on other models.



Auxiliary IP66 rated 240V and 415V/50Hz power outlets with ELCB protection provide power for additional tools or site lighting, while protecting workers.



ECO offers flexibility, reduced noise, exhaust emissions and fuel reduction via its automatic idle control.



Lockable single-side service access with battery lockout. All components of the generator and diesel engine are readily accessible, and replacing filters and other consumables is simple. External drains are conveniently placed for easy access.

Shindaiwa's DGW Series welders can get the job done.

The Japanese designed and built DGW series welder is the professional choice for mining, construction, rail, pipeline, automotive and a host of other welding applications. The DGW series is a proven, quality investment that's rapidly becoming the preferred option for rental fleets, major contractors, and owners of capital equipment.

Thanks to Shindaiwa's Ultra Quiet technology, the compact DGW series works silently in restricted spaces, or noise sensitive environments.

The engineered, sound absorbing and weatherproof canopy reduces noise levels down to 57dB(A)*, while still providing superior air flow and optimum engine cooling. A standard auxiliary power supply runs additional tools or lights. Factory fitted Voltage Reduction Devices (VRD), Real Dual operator modes and Earth Leakage Circuit Breaker (ELCB) protected 240/415V outputs up to 18kVA* keep workers safe.

Shindaiwa's ECO efficiency technology further reduces noise, along with fuel consumption, through continuous measurement of the weld cycle and operator requirements. Simply put, ECO controls the engine speed based on the required current to minimize noise levels and overall fuel consumption.


When you demand a rugged, reliable machine that keeps performing day in and day out, the Shindaiwa DGW SERIES has you covered.



Ultra-Quiet is a unique technology that minimises generator sound levels. An engineered enclosure, coupled with the use of specifically designed air

dams and noise absorbent insulated panels, redirects the cooling air. This doubles the distance air must travel through the enclosure, significantly reducing engine noise.

All Shindaiwa generator enclosures feature thicker panels – with special attention to the door panels, engineered sound absorbing foam and hardware. The result is lower sound levels as well as increased unit rigidity. A specially tuned muffler, plus the longer internal exhaust pipe achieve an improved balance of high and low noise frequencies.



WELDERS



Welding Generator		DGW201DM/ANZ	DGW300MS/ANZ
Rated current	A	170 / 190	260
Rated voltage	V	26.8 / 27.6	30.4
Duty cycle	%	50	80
Rated speed	min-1	3000 / 3600	3000
No load voltage	V	Max 80	Max 85
Current adj. range	A	60-180 / 50-200	Eco 30-300
			Auto/High 35-300
Welding rod dia.	mm	2.0 - 4.0	2.0 - 6.0

AC Generator			
Rated frequency	Hz	50 / 60	50
Rated speed	min-1	3000 / 3600	3000
Phase		1 Phase	1 Phase
Rated voltage	V	240	240
Power factor		1	1
Rated output	kVA	4.8	7.2
Outputs	A	1 x 20	2 x 15
Rating		Continuous	

Engine			
Model		Kubota Z482-B	Kubota D722
Type		Diesel, indirect injection, liquid cooled	
Number of cylinders		2	3
Displacement	L	0.479	0.719
Rated output	kW	7.8 / 9.2	11.7
Rated speed	RPM	3000 / 3600	3000
Emissions rating		Tier 3 ¹	-
Lubricant capacity	L	2.05	3.0 (effective 1.4)
Starting method		12V Electric start	
Battery		44B19L	46B24L

Dimensions and weight			
Dimensions (LxWxH)	mm	998 x 603 x 773	1400 x 600 x 850
Dry weight	kg	212	370
Fuel tank capacity	L	15	38
Coolant capacity	L	2.8	3.0 (inc. sub tank)
Noise level	dB(A)	58	57

1. Construction Machinery Gas Emission Regulation Standard by Ministry of Construction (Japan)
2. Construction Machinery Gas Emission Regulation Standard by Ministry of Construction (Japan); EPA (USA)
3. Construction Machinery Gas Emission Regulation Standard by Ministry of Construction (Japan); Stage 3A (EU)

Welding Generator		DGW420DM/ANZ	DGW500DM/ANZ			
Operation		Single	Dual	Single	Dual	
CC Mode	Rated current	A	390	200	480	230
	Rated voltage	V	35.6	28.0	39.2	29.2
	Duty cycle	%	60	100	60	80
	Current adj. range	A	95 - 400	50 - 210	60 - 500	30 - 280
	Welding rod dia.	mm	2.6 - 8.0	2.0 - 4.0	2.6 - 8.0	2.0 - 6.0
	Gouging rod dia.	mm	3.2 - 8.0	3.2 - 5.0	3.2 - 9.5	3.2 - 5.0
CV Mode	Rated current	A	350	200	480	230
	Rated voltage	V	32.5	21.0	39.0	22.5
	Duty cycle	%	100	100	60	80
	Voltage adj. range	V	14 - 35	14 - 23.5	14 - 40	14 - 29
Welding wire dia.	mm	0.6 - 2.0	0.6 - 1.6	0.6 - 2.4	0.6 - 2.0	
Rated speed	min-1	3000				
No load voltage	V	Max 85				

AC Generator					
Rated frequency	Hz	50			
Rated speed	min-1	3000			
Phase		1 Phase	3 Phase	1 Phase	3 Phase
Rated voltage	V	240	415	240	415
Power factor		1.0	0.8	1.0	0.8
Rated output	kVA	10.8	14.0	10.8	15
Outputs	A	3 x 15	1 x 20	3 x 15	1 x 20
Rating		Continuous			

Engine			
Model		Kubota D1105	Kubota V1505
Type		Diesel, direct injection, liquid cooled	
No. of cylinders		3	4
Displacement	L	1.123	1.498
Rated output	kW	18.5	24.5
Rated speed	RPM	3000	
Emissions rating		Interim Tier 4 ²	Tier 3 ³
Lubricant capacity	L	5.1	6.0
Starting method		12V Electric start	
Battery		55B24L	75D31R

Dimensions and weight			
Dimensions (LxWxH)	mm	1435 x 700 x 848	1680 x 700 x 950
Dry weight	kg	480	613
Fuel tank capacity	L	43	63
Coolant capacity	L	4.3 (inc. sub. tank)	5.8 (inc. sub. tank)


Accessories and optional fit ups

Shindaiwa offers site or rental specific optional features tailored to your environment.

- Safety roll frames for easy site maneuverability and added machine protection;
- Bunded base to eliminate and contain spillage;
- Exhaust spark arrestor to limit the possibility of site ignition;
- Waterproof document holder to protect operator and service records;
- Battery trickle feeder to maintain the health of your battery;

- Fitment of an approved fire extinguisher for personal safety.

Simply specify what you need and we will deliver a site-ready unit ready to perform to your requirements.



construction

On site, if the power stops, everything stops. And costs start mounting up. Shindaiwa's rugged, compact, sound-attenuated generator welders provide clean, reliable power for all kinds of welding applications. Precise control over current and voltage help guarantee precision welds every time, and earth leakage and VRD protection ensures safe operation in all conditions.

Welding in any mining application is a high-risk activity. Shindaiwa generator welders are specifically designed to provide maximum operational safety. Earth leakage and VRD protection, together with auto output reduction, keep operators safe, and production running at maximum capacity in the toughest conditions.

mining